



Automatic

# BREVIS

Cut the effort.  
Keep the performance.

C-One Brevis is a low turntable designed to create compact, efficient end-of-line systems without the need for expensive pallet lifters. Brevis answers a clear market need: bringing automation to environments where space is limited and pallets are handled by hand or pallet truck. The machine is a rotary table stretch wrapper equipped with integrated inlet and outlet roller conveyors. Pallets are manually loaded onto the infeed conveyor by the operator using a pallet truck, then automatically transferred to the wrapping area. After the wrapping cycle, the pallet is moved to the outfeed conveyor following a simple operator command, ensuring a smooth and controlled workflow. Safety is built into the design. TÜV-checked for safety compliance, it operates without the need for safety fences, offering protection while maintaining full accessibility. Flexible and scalable, it can be configured with horseshoe conveyors and integrated control solutions, adapting perfectly to different line requirements. Compact, affordable, and highly efficient, C-One Brevis brings automation where it was not possible before.

#### Technical Data

- ↓ Height: **2690 mm** Max: **2892 mm**
- ↔ Width: **3136 mm**
- ↗ Length: **4445 mm**
- ⤷ Turntable Height: **90 mm**
- 📦 Weight: **1150 Kg**
- ⚡ Power supply: **230 VAC**
- ⚡ Power absorption: **2 kW**



# BREVIS

## PRODUCT SPECIFICATIONS

- PLC for the management of the cycle
- Frequency controller for carriage speed adjustment
- Frequency controller for turntable speed adjustment
- Loading plate ø 1650 mm or Ø1800 as an optional
- Maximum height of pallet:  
2200 mm or 2800 mm as an optional
- Maximum size of the pallet: 800x1200 mm  
or 1000x1200 with Ø1650 mm turntable or 1200x1200  
with Ø1800 mm turntable
- Maximum loading weight: 1200 kg
- Pre-stretch carriage
- Photocell for pallet height detection
- Safety stop at the base of the carriage
- Infeed and Outfeed conveyors aligned  
or rotated 90° each other
- Lock password  
(parameters values can be modified only entering a password)
- Adjustable parameters by the control panel:  
cycle selection, bottom laps, top laps,  
parameters, rotation speed, carriage ascent speed,  
carriage descent speed, film tension
- 4 working cycles: ascent/descent; topsheet;  
only ascent; layers
- Storage of 10 end user programs
- 1 working way: semiautomatic
- Strengthening operation
- Acoustic warning at the cycle start and stop
- Autodiagnostic
- Wrapped pallet counter
- Powder coating
- Braked turntable at the end of the cycle

## MAIN OPTIONS

- Top-press
- Touch screen panel
- Adjustable power pre-stretch
- 3000mm max wrapping height
- 2000mm turntable
- Photocell for dark loads
- Safety fences
- 90° stop
- Ramp for UK pallet
- Infeed/Outfeed low roller conveyors



Control Panel



Mechanical Clamp



Turntable Conveyor



C&C group s.r.l.  
via Calcinaro 2071  
47521 Cesena (FC) - Italy  
+39 (0)547 324747

P.IVA e Cod. Fisc. 03434700401  
SDI: T04ZHR3  
PEC: cecgroupsrl@pec.it  
info@cecgroupsrl.com

[www.cecgroupsrl.com](http://www.cecgroupsrl.com)