



Semi-Automatic

BASE

Precision wrapping,
on your terms.

C-One Base is designed for businesses that demand flexibility, precision, and full control over their end-of-line packaging process. Built as a premium turntable solution, it combines advanced technology with intuitive operation to handle a wide range of wrapping needs.

At its core, the All Shortcuts (AS) electronic board allows quick access to all key parameters, making setup and adjustments fast and straightforward. Operators can fine-tune every phase of the cycle with accuracy, ensuring optimal wrapping results across different load types.

From standard pallets to demanding and unstable loads, Base is built to adapt, cycle after cycle.

Its wide range of configurable parameters and advanced functions allows you to tailor every wrapping program to your specific application, ensuring optimal performance in any condition. Designed to sustain high working rates, C-One Base is a highly customizable solution that grows with your production needs, delivering consistent results even under intensive workloads.

Technical Data

- ↕ Height: **2580 mm**
- ↔ Width: **1500 mm**
- ↗ Length: **2865 mm**
- ↻ Turntable Height: **75 mm**
- 📦 Weight: **420 Kg**
- ⚡ Power supply: **230 VAC**
- ⚡ Power absorption: **0.75 / 1 kW**



www.cecgrouprl.com

BASE

PRODUCT SPECIFICATIONS

- Electronic printed circuit board for the management of the cycle
- Frequency controller for carriage speed adjustment
- Frequency controller for turntable speed adjustment
- Loading plate ø 1500 mm
- Maximum height of pallet: 2200 mm
- Maximum size of the pallet: 800x1200 mm
- Maximum loading weight: 1200 kg
- Electromagnetic brake for the stretching of the film
- Photocell for pallet height detection
- Safety stop at the base of the carriage
- Stop at 0 position
- Power board IP54
- 3 password levels (including lock password)
- Adjustable parameters by the control panel without password: cycle selection, bottom laps,
- top laps, topsheet cycle parameters, rotation speed, carriage ascent speed, carriage descent speed, film tension, starting wrapping height
- Quick selection of 6 main parameters or saved programs;
- Usb port to upload software and download settings and reports;
- Statistics.
- 6 working cycles: ascent/descent; topsheet; only ascent; only descent; layers; stack
- Storage of 32 end user programs
- 3 working ways: semimanual, semiautomatic, fixed height
- Strengthening operation
- Acoustic warning at the cycle start and stop
- Autodiagnostic
- Wrapped pallet counter
- Powder coating
- Braked turntable at the end of the cycle
- 2 years warranty

MAIN OPTIONS


- Touch screen panel
- Top-press
- Adjustable power pre-stretch
- Power pre-stretch with auto cut-off system
- Roping system
- 3000 mm max wrapping height
- 1650 mm turntable
- 1800 mm turntable
- 2000 kg max pallet weight
- Remote control
- Ramp
- Pit frame
- Photocell for dark loads
- Clip to tie the film to the turntable
- Weighing system
- Mechanical system to brake roll containers
- Feet under the machine
- Safety fences
- Icy kit

C&C group s.r.l.
via Calcinaro 2071
47521 Cesena (FC) - Italy
+39 (0)547 324747

P.IVA e Cod. Fisc. 03434700401
SDI: T04ZHR3
PEC: cecgroupsrl@pec.it
info@cecgroupsrl.com



Control Panel



Power Pre-Stretch Carriage



Mechanical Clamp



www.cecgroupsrl.com