

VENOR

The efficiency hunter.

Meet **Venor**, the latest evolution in pallet wrapping by C&C. Inspired by the Latin "venator", meaning hunter, Venor was created with one mission: to seek out inefficiencies in your packaging process and eliminate them with precision. Smart, autonomous and remarkably agile, it thrives in demanding logistics environments, adapting smoothly to different pallets, workflows and warehouse layouts. Venor is not just here to work; it is here to change the way we think about wrapping.

Entirely made of steel, engineered for durability, stability and accuracy, it reflects our approach to innovation: practical, reliable and built to last. It is not just another machine, it is the result of engineering meeting intuition, and of every department working side by side to build something ready for the future Technical data.

Technical Data

- ↓ Height: **2457 mm**
- ↔ Width: **1343 mm**
- ↗ Length: **1545 mm**
- 📦 Weight: **350 Kg**
- ⚡ Power supply: **24 V**
- ⚡ Power absorption: **1,2 kW**



VENOR

PRODUCT SPECIFICATIONS

- ➔ Electronic printed circuit board for the management of the cycle
- ➔ Frequency controller for rotation speed adjustment (from 1,8 km/h to 4,9 km/h)
- ➔ Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- ➔ Maximum wrapping height: 2200 mm
- ➔ Maximum size of the pallet: unlimited
- ➔ Electromagnetic brake for film stretching
- ➔ Photocell for pallet height detection
- ➔ Safety stop at the base of machine
- ➔ Power board IP21
- ➔ Main parameters protected by password
- ➔ Main parameters adjustable by the control panel: cycle selection, bottom wraps, top wraps, rotation speed, carriage speed going up, carriage speed going down, film tension, photocell delay, starting height
- ➔ Reinforcing operation
- ➔ Working cycles: up/down; topsheet; only ascent; only down
- ➔ 20 programs can be saved by the customer
- ➔ 3 working ways: manual, semiautomatic, fixed height
- ➔ Acoustic warning at the cycle beginning and stop
- ➔ Battery charge monitoring and warning message on the display when the battery is low
- ➔ Touching wheel with quick height adjustment
- ➔ Autodiagnostic
- ➔ Advanced battery charger with efficiency > 85%, charging process fully controlled by microprocessor, automatic reset after connecting a new battery, protection against polarity inversion and short circuits, autodiagnostic, compensation of the voltage drop on the battery cables, normally closed power contact
- ➔ Powder coating
- ➔ Auto switch-off to save battery
- ➔ 2 years warranty (batteries excluded)

MAIN OPTIONS

- ➔ Touch screen panel
- ➔ Dynamic safety system
- ➔ Power pre-stretch carriage
- ➔ Flashing lamp
- ➔ Double wheel
- ➔ Photocell for dark loads



C&C group s.r.l.
via Calcinaro 2071
47521 Cesena (FC) - Italy
+39 (0)547 324747

P.IVA e Cod. Fisc. 03434700401
SDI: T04ZHR3
PEC: cecgroupsrl@pec.it
info@cecgroupsrl.com

www.cecgroupsrl.com